

**Sabiedrība ar ierobežotu atbildību "RSG"**  
**Reģistrācijas numurs LV40203342637**  
**A/S SWEDBANK HABALV22**  
**LV50HABA0551051323272**

**Email: [info@rsg.lv](mailto:info@rsg.lv)**

**Tel/Whatsapp: [+371 20 45 80 80.](tel:+37120458080)**

**[WWW.RSG.LV](http://WWW.RSG.LV)**

**REVOLUTIONARY  
POINT FITTINGS COSMO**

**GLASS<sup>®</sup>**  
GLASS FITTINGS

***FOLLOW US ON***



## SATIN

## BLACK CHROME

## BLACK MAT

DIAMETER  $\varnothing$  34 MM  
DISTANCE 30 MM



COS-3430-304



COS-3430-304-B

DIAMETER  $\varnothing$  48 MM  
DISTANCE 30 MM



COS-4830-304

COS-4830-316 SS 316L



COS-4830-304-B



COS-4830-3040-MB

DIAMETER  $\varnothing$  48 MM  
DISTANCE 40 MM



COS-4840-304




COS-4840-304-B



COS-4840-3040-MB

DIAMETER  $\varnothing$  48 MM  
DISTANCE 50 MM



COS-4850-304



COS-4850-304-B

STANDARD MATERIAL **SS 304**

## WHY IS IT THE BEST POINT FITTING ?



SAVE TIME



SAVE MONEY



CUSTOMER SATISFACTION

### 4 FUNCTIONS TO SIMPLIFY THE INSTALLATION OF GLASS BALUSTRADE



EASY POSITIONING  
RELATIVE TO THE  
HOLE IN THE GLASS  
DUE TO BEANS IN THE  
BASE OF FIXING.



SMOOTH ADJUSTMENT  
OF DISTANCE FROM THE  
FRONT OF THE  
BALUSTRADE AFTER  
GLASS APPLICATION.  
WE APPLY THE GLASS  
ONLY ONCE!

IN THE CASE OF FIXING TO THE  
GROUND WITH A HEX HEAD SCREW.  
DURING GLASS INSTALLATION,  
M12 THREAD IN THE NECK ALLOWS  
PUTTING A HEX KEY INSIDE TO LOOSEN  
THE SCREW AND ADJUST THE  
POSITION OF THE FIXING RELATIVE TO  
THE HOLE IN THE GLASS.



HEXAGONAL HEAD SCREW ALLOWS FOR STRONG  
TIGHTENING.  
THE COVER IS INSTALLED AS THE LAST STEP.  
AESTHETIC APPEARANCE THANKS TO HIDDEN  
BOLTS.